



# 15W筒灯模组规格书

## 15W Down light Module Specification

15W筒灯模组 15W Down Light Module		
分类 Class	项目 Item	LEDL-220V-15W-GG-V1-R1-H
电参数 Electrical Parameter	输入电压 (V) Input	AC 198-242V
	功率 (W) Powe	15W (@220V)
	功率因数 Power Factor	>0.95
	调光 & 频闪 Dimming & Flicker	NA
	电源谐波 (%) THD	<15%
	浪涌能力 Surge Tolerance	1KV 浪涌测试 1KV Surge Test
	灯具类别 Luminaire Class	1类 Class I
	绝缘耐压 (V) Withstand Voltage(V)	1.5KV (AC)
光参数 Optical Parameter	流明输出 (lm) Lumens Output (lm)	1500Lm
	色温 (K) CCT (K)	4000K/5000K
	显色性 (Ra)	Ra80
	配光 Light Distribution	灯珠均匀排列 <b>LED Even Aligned</b>
规格 Parameter	尺寸 (mm) Dimension	直径100mm
	灯珠规格 LED	SMD 2835 - 9V
	基板材质 Base Board	1.2mm 铝基板 导热系数>1.5 1.2mm Al MCPCB Thermal resistance>1.5
环境与 安全 Environment	LED 热阻 LED Thermal Resistance	12° C/W
	工作温度 Work Temperature	-40~85° C (基板温度) (PCB Temperature)
标准 Certification		CCC CE
寿命 Life Time		>30000小 时>30000

