

100W工矿灯模组 100W High Bay

分类 Class	项目 Item	LEHB-220V-100W
电参数 Electrical Parameter	输入电压 (V) Input	AC 198-242V
	功率 (W) Powe	100W (@220V)
	功率因数 Power Factor	>0.98
	调光 Dimming	NA
	电源谐波 (%) THD	<15%
	浪涌能力 Surge Tolerance	2KV 浪涌测试 2KV Surge Test
	灯具类别 Luminaire Class	1类 Class I
	绝缘耐压 (V) Withstand Voltage(V)	1.5KV(AC)
光参数 Optical Parameter	流明输出 (lm) Lumens Output(lm)	12000Lm
	色温 (K) CCT (K)	冷白 自然白 暖白 Cool White, Natural White, Warm White
	显色性 (Ra)	Ra70
	配光 Light Distribution	灯珠均匀排列 LED Even Aligned
规格 Parameter	尺寸 (mm) Dimension	直径 168mmDiameter
	灯珠规格 LED	3030 - 6V
	基板材质 Base Board	1.5mm 铝基板 导热系数>1.5 1.5mm Al MCPCB Thermal resistance>1.5
环境与 安全 Environment	LED 热阻 LED Thermal Resistance	6° C/W
	工作温度 Work Temperature	-40~85° C (基板温度) (PCB Temperature)
标准 Certification	GB7000.1-2007 灯具第一部分 一般要求与试验 CCC CE	
寿命 Life Time	>30000小 时>30000	

